

New

Vehicle DVR 4CH>>> SA-4060C



Features


- Compliances with Automotive Industry and the Voltage Ranges for All
- Easy Swapped HDD Tray in Front
- 2.5" SATA HDD and SSD HDD Support
- Certified 1.0G HDD Anti-Shock Design Patent
- Extreme Temperature and Ruggedness Approved for Installation in All Cars
- Most Reliable MJPEG Chip 5 Years Working Guaranty
- Synchronization Video Recording and Hidden Audio Recording Support
- Continuous Recording, Motion Recording and Schedule Recording
- Hard Drive Indicator on Fascia
- Prompt Recording upon Boot-up
- Ending File Protection While Unexpected Power Cut
- Power Restored Recording Restored
- FUHO Made Cameras Power Supplied by DVR

Specifications

Item	Description	
Video Format	NTSC/PAL	
OS	Embedded RTOS	
Video Input	x4 BNC 1Vp-p 75Ω	
Video Output	x2 BNC Monitor Output	
Audio Input	x1 RCA	
Audio Output	x1 RCA	
Menu Interface	Multi-lingual Option	
Live Frame Rate	NTSC	120fps (4 x 30fps)
	PAL	100fps (4 x 25fps)
Recording Frame Rate	NTSC	60fps
	PAL	50fps
Retrieving Mode	Duplex (Recording & Playback)	
Resolution	Live	NTSC 640 x 480
		PAL 640 x 544
	Recording	NTSC 640 x 240
		PAL 640 x 272
Compression	Modified MJPEG	Normal 12K Bytes/Frame
		High 12K Bytes/Frame
		Highest 12K Bytes/Frame
Hard Drive	2.5" SATA Hard Drive x1	
Search	Mode	Time/Date & Event List
	Full Screen	Yes
Alarm Input	Yes	
Motion Detection	Yes	
Video Loss Alert	Yes	
Auto Channel Cycling	Yes	
Buzzard Alert	Yes	
Brightness Adjustment	Yes	
Contrast Adjustment	Yes	
Air Connectors	x4 Camera Video Input Cable (12VDC Max. 0.5A)	
System Monitor	Power Restored Recording Restored	
Power Input	8VDC ~ 28VDC	
Dimensions	195mm x 265mm x 65mm (L x W x H)	
Weight	2.8KG (HDD Included)	
Shock Factor	1.0G	
Operating Temperature	-15°C~ +70°C	

Car Bracket

Unit Bedded (Bracket Option)



Unit Slung (Bracket Option)

